

Model		Adjustable range (A)		Contactor compatible	Dimensions
	JRS2 12.5/Z	0.16-0.25 0.25-0.4 0.4-0.63 0.63-1 0.8-1.25 1-1.6 1.25-2 1.6-2.5	2-3.2 2.5-4 3.2-5 4-6.3 5-8 6.3-10 8-12.5 10-14.5	CJX1-09-22	
	JRS2 25/Z	1-1.6 1.6-2.5 2-3.2 2.5-4 3.2-5 4-6.3	5-8 6.3-10 8-12.5 10-16 12.5-20 16.25	CJX1-16-22	
	JRS2 45/Z	6.3-10 10-16 12.5-20 16-25 20-32 32-40		CJX1-32-38	
	JRS2 80/Z	20-32 32-50 50-63 63-80		CJX1-45-85	
	JRS2 135/Z	55-80 63-90 80-110 90-120 110-135		CJX1-110-140	
	JRS2 180/Z	55-80 63-90 90-120 120-150 150-180		CJX1-170-205	
	JRS2 400/F	160-250 200-320 250-400 320-500 400-630		CJX1-250-400	

Contactors de auxiliary

mechanical interlock

Conformity to IEC 60947-4/VDE660		
Model	JZC1-22	JZC1-44
voltage (Ui)	660V	
Currente nominal	10 A	
contactors	2NO+2NC	4NO+4NC
Manobras	3000	
Voltage (coil)	24Vac.110Vac.220Vac / 380Vac	

Model Available
CJX1-32/38
CJX1-45/63
CJX1-75/85
CJX1-110/140
CJX1-170/205
CJX1-250/300
CJX1-400



JZC1